

**FAG****11207-TVH>J**

Self-aligning ball bearing

Self-aligning ball bearing 112...-TVH, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>J	Not marked on bearing
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	72 mm	Outside diameter
B	52 mm	Total width
B _C	17 mm	Width, outer ring
B _i	52 mm	Width, inner ring
C _r	16.000 N	Basic dynamic load rating, radial
C _{0r}	5.100 N	Basic static load rating, radial
C _{ur}	325 N	Fatigue load limit, radial
n _G	11.600 1/min	Limiting speed
n _{gr}	9.800 1/min	Reference speed
m	0,54 kg	Masa

Mounting dimensions

D _{a max}	65 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximaler Hohlkehlradius



Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
D_1	59,08 mm	Shoulder diameter outer ring
d_1	47,7 mm	Shoulder diameter inner ring
b	7 mm	Width retaining slot
t	9 mm	Hight retaining slot

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

e	0,22	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,81	Dynamic axial load factor
Y_2	4,35	Dynamic axial load factor
Y_0	2,94	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna