




FAG

16044-C4

Deep groove ball bearing

Deep groove ball bearing 160, single row,
steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	340 mm	Outside diameter
B	37 mm	Width
C _r	198.000 N	Basic dynamic load rating, radial
C _{0r}	240.000 N	Basic static load rating, radial
C _{ur}	8.600 N	Fatigue load limit, radial
n _G	2.600 1/min	Limiting speed
n _{gr}	2.310 1/min	Reference speed
≈m	11,8 kg	Masa



Mounting dimensions

$d_{a\min}$	230,2 mm	Minimum diameter shaft shoulder
$D_{a\max}$	329,8 mm	Maximum diameter of housing shoulder
$r_{a\max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
D_1	298,05 mm	Shoulder diameter outer ring
d_1	262,8 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	16,3	Calculation factor
-------	------	--------------------

Właściwości

-  F_r Obciążenie promieniowe
-  F_a Obciążenie osiowe jednokierunkowe
-  F_a Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe