

FAG

2200-2RS-TVH

Self-aligning ball bearing

Self-aligning ball bearing 22..-2RS-TVH,
seals, plastic cage

Informacje techniczne





Twoja aktualna wersja produktu

Bore type	Z	Cylindrical
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubricant	GA14	Ball bearing grease, low noise

Main Dimensions & Performance Data

d	10 mm	Bore diameter
D	30 mm	Outside diameter
B	14 mm	Width
C_r	5.700 N	Basic dynamic load rating, radial
C_{0r}	1.190 N	Basic static load rating, radial
C_{ur}	76 N	Fatigue load limit, radial
n_G	17.600 1/min	Limiting speed
≈m	48,2 g	Masa

Mounting dimensions

$d_{a\ min}$	14,2 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	25,8 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,6 mm	Maximum fillet radius

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Dimensions

r_{min}	0,6 mm	Minimum chamfer dimension
D_1	23,081 mm	Shoulder diameter outer ring
D_2	25,17 mm	Caliber diameter outer ring
d_1	16,25 mm	Shoulder diameter inner ring
d_2	14,1 mm	Caliber diameter inner ring

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y_1	1,96	Dynamic axial load factor
Y_2	3,03	Dynamic axial load factor
Y_0	2,05	Static axial load factor

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Obciążenie osiowe dwukierunkowe
- Smarowanie dożywotnie, bezobsługowe
- Smarowanie smarem
- Uszczelnienie dwustronne
- Nieosiowość statyczna
- Nieosiowość dynamiczna

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje