



FAG



23048-BE-XL-H151B

Spherical Roller Bearing

Spherical roller bearing 230...-BE-XL-H151B, symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	
Locating feature, bearing outer ring	H151B	2 Locking features, bearing outer ring

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	360 mm	Outside diameter
B	92 mm	Width
C _r	1.350.000 N	Basic dynamic load rating, radial
C _{0r}	2.120.000 N	Basic static load rating, radial
C _{ur}	200.000 N	Fatigue load limit, radial
n _G	2.080 1/min	Limiting speed
n _{gr}	1.310 1/min	Reference speed
m	32,6 kg	Masa



Mounting dimensions

d _{a min}	252,4 mm	Minimum diameter shaft shoulder
D _{a max}	347,6 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	324,6 mm	Bore diameter outer ring
d ₂	269,5 mm	Raceway diameter of the inner ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,98	Dynamic axial load factor
Y ₂	4,44	Dynamic axial load factor
Y ₀	2,92	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna