



FAG


23130-E1A-XL-K-M-C3

Spherical Roller Bearing

Spherical roller bearings 231...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	
Special material	Standard	

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	250 mm	Outside diameter
B	80 mm	Width
C _r	1.000.000 N	Basic dynamic load rating, radial
C _{0r}	1.330.000 N	Basic static load rating, radial
C _{ur}	145.000 N	Fatigue load limit, radial
n _G	2.650 1/min	Limiting speed
n _{gr}	1.720 1/min	Reference speed

≈m	15,069 kg	Masa
----	-----------	------



Mounting dimensions

d _{a min}	162 mm	Minimum diameter shaft shoulder
D _{a max}	238 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius
d _{a max}	170 mm	Maximum diameter of shaft shoulder
d _{b min}	160 mm	Minimum cavity diameter of the sleeve
B _{a min}	8 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
D ₁	220,8 mm	Bore diameter outer ring
d _s	6,3 mm	Diameter lubrication hole
n _s	12,2 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,29	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,32	Dynamic axial load factor
Y ₂	3,45	Dynamic axial load factor
Y ₀	2,26	Static axial load factor

Additional information

H3130	Adapter sleeve
AHX3130G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna