


FAG

23148-BE-XL-C3 [🔗](#)  
Spherical Roller Bearing

Spherical roller bearing 231...-BE-XL,  
symmetric with rib washer


X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BE           | With lose center lip ring         |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | JPB          | Sheet metal cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication feature     | Standard     |                                   |



Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 240 mm      | Bore diameter                     |
| D               | 400 mm      | Outside diameter                  |
| B               | 128 mm      | Width                             |
| C <sub>r</sub>  | 2.130.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 3.150.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 255.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.700 1/min | Limiting speed                    |
| n <sub>gr</sub> | 970 1/min   | Reference speed                   |
| ≈m              | 62,245 kg   | Masa                              |



Mounting dimensions

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 257 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 383 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 3 mm   | Maximum recess radius                |

Dimensions

|                  |          |                                    |
|------------------|----------|------------------------------------|
| r <sub>min</sub> | 4 mm     | Minimum chamfer dimension          |
| D <sub>1</sub>   | 349,9 mm | Bore diameter outer ring           |
| d <sub>2</sub>   | 275,9 mm | Raceway diameter of the inner ring |
| d <sub>s</sub>   | 9,5 mm   | Diameter lubrication hole          |
| n <sub>s</sub>   | 17,7 mm  | Width of lubricating groove        |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,31 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 2,18 | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 3,24 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 2,13 | Static axial load factor                                                         |



## Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna