



FAG



23192-BEA-XL-MB1-H151B

Spherical Roller Bearing

Spherical roller bearing 231...-BEA-XL-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	
Locating feature, bearing outer ring	H151B	2 Locking features, bearing outer ring

Main Dimensions & Performance Data

d	460 mm	Bore diameter
D	760 mm	Outside diameter
B	240 mm	Width
C _r	6.900.000 N	Basic dynamic load rating, radial
C _{0r}	11.500.000 N	Basic static load rating, radial
C _{ur}	760.000 N	Fatigue load limit, radial
n _G	770 1/min	Limiting speed
n _{gr}	395 1/min	Reference speed
m	433,5 kg	Masa



Mounting dimensions

$d_{a \min}$	492 mm	Minimum diameter shaft shoulder
$D_{a \max}$	728 mm	
$r_{a \max}$	6 mm	Maximum recess radius

Dimensions

$r_{\min}$	7,5 mm	Minimum chamfer dimension
D_1	663,4 mm	Bore diameter outer ring
d_s	12,5 mm	Diameter lubrication hole
n_s	23,5 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,31	
Y_1	2,21	Dynamic axial load factor
Y_2	3,29	Dynamic axial load factor
Y_0	2,16	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna