

FAG


## 23226-E1A-XL-K-M

### Spherical Roller Bearing

Spherical roller bearings 232...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

## Informacje techniczne



### Twoja aktualna wersja produktu

|                           |              |                           |
|---------------------------|--------------|---------------------------|
| Design                    | E1A          | Without central rip       |
| Bore type                 | K            | Tapered, taper 1:12       |
| Cage                      | M            | Brass Cage                |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication feature     | Standard     |                           |

### Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 130 mm      | Bore diameter                     |
| D               | 230 mm      | Outside diameter                  |
| B               | 80 mm       | Width                             |
| C <sub>r</sub>  | 910.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.150.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 91.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.850 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.740 1/min | Reference speed                   |
| ≈m              | 13,57 kg    | Masa                              |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 144 mm | Minimum diameter shaft shoulder       |
| $D_{a \max}$ | 216 mm | Maximum diameter of housing shoulder  |
| $r_{a \max}$ | 2,5 mm | Maximum recess radius                 |
| $d_{a \max}$ | 152 mm | Maximum diameter of shaft shoulder    |
| $d_{b \min}$ | 142 mm | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 21 mm  | Minimum cavity width of the sleeve    |

### Dimensions

|            |          |                             |
|------------|----------|-----------------------------|
| $r_{\min}$ | 3 mm     | Minimum chamfer dimension   |
| $D_1$      | 199,3 mm | Bore diameter outer ring    |
| $d_s$      | 4,8 mm   | Diameter lubrication hole   |
| $n_s$      | 9,5 mm   | Width of lubricating groove |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,33 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,07 | Dynamic axial load factor                                                            |
| $Y_2$ | 3,09 | Dynamic axial load factor                                                            |
| $Y_0$ | 2,03 | Static axial load factor                                                             |

### Additional information

|          |                   |
|----------|-------------------|
| H2326    | Adapter sleeve    |
| AHX3226G | Withdrawal sleeve |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna