



FAG

234424-M-SP

Axial angular contact ball bearing

Axial angular contact ball bearings 2344, double direction, separable, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	180 mm	Outside diameter
B	72 mm	Width
C	36 mm	Width, outer ring
C _a	101.000 N	Basic dynamic load rating, axial
C _{0a}	350.000 N	Basic static load rating, axial
C _{ua}	26.000 N	Fatigue load limit, axial
n _{G Grease}	3.200 1/min	Limiting speed for grease lubrication
n _{G Oil}	4.300 1/min	Limiting speed for oil lubrication
≈m	5,81 kg	Masa



Mounting dimensions

d _a	144,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	170 mm	Shoulder diameter outer ring
D _a	H12	Shoulder diameter outer ring clearance
r _a max	2 mm	Maximum recess radius
r _{a1} max	0,6 mm	Maximum recess radius
α	60 °	Contact angle
a	300 mm	Distance between the apexes of the pressure cones

Dimensions

d ₁	160 mm	Rip diameter shaft washer
B ₁	18 mm	Height wave disc
r _{min}	2 mm	Minimum chamfer dimension
r ₁ min	0,6 mm	Minimum chamfer dimension
d _s	4,8 mm	Diameter lubrication hole
n _s	9,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

c _a	996 N/μm	Axial rigidity
K _{aE}	2.736 N	Lift-off force
F _v	960 N	Preload force



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia