





FAG

23964-K-MB-C5

Spherical Roller Bearing

Spherical roller bearing 239...-K-MB,
symmetric 3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	C5 (Group 5)	Internal clearance larger than C4
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	440 mm	Outside diameter
B	90 mm	Width
C _r	1.310.000 N	Basic dynamic load rating, radial
C _{0r}	2.750.000 N	Basic static load rating, radial
C _{ur}	206.000 N	Fatigue load limit, radial
n _G	1.700 1/min	Limiting speed
n _{gr}	930 1/min	Reference speed
m	39,415 kg	Masa

Mounting dimensions

d _{a min}	332,4 mm	Minimum diameter shaft shoulder
D _{a max}	427,6 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius
d _{a max}	349 mm	Maximum diameter of shaft shoulder
d _{b min}	332 mm	Minimum cavity diameter of the sleeve
B _{a min}	12 mm	Minimum cavity width of the sleeve



Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	406,2 mm	Bore diameter outer ring
d _s	9,5 mm	Diameter lubrication hole
n _s	17,7 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,19	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,62	Dynamic axial load factor
Y ₂	5,39	Dynamic axial load factor
Y ₀	3,54	Static axial load factor

Additional information

H3964-HG	Adapter sleeve
AH3964G-H	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna