



FAG

23968-MB-C2

Spherical Roller Bearing

Spherical roller bearing 239...-MB, symmetric
3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

Bore type	Z	Cylindrical
Cage	MB	Solid brass cage
Radial internal clearance	C2 (Group 2)	Internal clearance smaller than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	460 mm	Outside diameter
B	90 mm	Width
C _r	1.370.000 N	Basic dynamic load rating, radial
C _{0r}	3.000.000 N	Basic static load rating, radial
C _{ur}	204.000 N	Fatigue load limit, radial
n _G	1.610 1/min	Limiting speed
n _{gr}	860 1/min	Reference speed
≈m	43,035 kg	Masa

Mounting dimensions

d _{a min}	352,4 mm	Minimum diameter shaft shoulder
D _{a max}	447,6 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius



Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	426,7 mm	Bore diameter outer ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,18	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,85	Dynamic axial load factor
Y_2	5,73	Dynamic axial load factor
Y_0	3,76	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna