



FAG

23992-B-MB-C3

Spherical Roller Bearing

Spherical roller bearing 239...-B-MB,
symmetric 3 ribs

Informacje techniczne



Twoja aktualna wersja produktu


Design	B	With fixed central rib
Bore type	Z	Cylindrical
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	460 mm	Bore diameter
D	620 mm	Outside diameter
B	118 mm	Width
C _r	2.270.000 N	Basic dynamic load rating, radial
C _{0r}	5.400.000 N	Basic static load rating, radial
C _{ur}	380.000 N	Fatigue load limit, radial
n _G	1.080 1/min	Limiting speed
n _{gr}	590 1/min	Reference speed
m	103,5 kg	Masa

Mounting dimensions

d _{a min}	474,6 mm	Minimum diameter shaft shoulder
D _{a max}	605,4 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius





Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	573,3 mm	Bore diameter outer ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,18	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,85	Dynamic axial load factor
Y ₂	5,73	Dynamic axial load factor
Y ₀	3,76	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna