

FAG



**24152-BE-XL-C4**

## Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,  
symmetric with rib washer

X-life

## Informacje techniczne



## Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BE           | With lose center lip ring         |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | JPB          | Sheet metal cage                  |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication feature     | Standard     |                                   |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 260 mm      | Bore diameter                     |
| D               | 440 mm      | Outside diameter                  |
| B               | 180 mm      | Width                             |
| C <sub>r</sub>  | 3.150.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 4.900.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 400.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.290 1/min | Limiting speed                    |
| n <sub>gr</sub> | 560 1/min   | Reference speed                   |
| ≈m              | 109,485 kg  | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a\ min}$ | 277 mm | Minimum diameter shaft shoulder      |
| $D_{a\ max}$ | 423 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 3 mm   | Maximum recess radius                |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 4 mm     | Minimum chamfer dimension          |
| $D_1$      | 370,6 mm | Bore diameter outer ring           |
| $d_2$      | 292,2 mm | Raceway diameter of the inner ring |
| $d_s$      | 8 mm     | Diameter lubrication hole          |
| $n_s$      | 15 mm    | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,4  | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 1,67 | Dynamic axial load factor                                                            |
| $Y_2$ | 2,49 | Dynamic axial load factor                                                            |
| $Y_0$ | 1,63 | Static axial load factor                                                             |



## Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna