



FAG

29414-E1-XL-N1

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL, no flanging ring

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	N1	Locating feature, housing washer
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	150 mm	Outside diameter
T	48 mm	Height
C _a	550.000 N	Basic dynamic load rating, axial
C _{0a}	1.290.000 N	Basic static load rating, axial
C _{ua}	154.000 N	Fatigue load limit, axial
n _G	5.000 1/min	Limiting speed
n _{gr}	2.430 1/min	Reference speed
≈m	3,6 kg	Masa



Mounting dimensions

$d_{a\ min}$	110 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	124 mm	Maximum diameter of housing shoulder
$D_{b\ min}$	153 mm	Minimum bore diameter housing
$d_{b\ max}$	78,5 mm	Maximum distance sleeve
$r_{a\ max}$	2 mm	Maximum recess radius

Dimensions

D_1	99 mm	Bore diameter housing washer
d_1	133,8 mm	Rip diameter shaft washer
r_{min}	2 mm	Minimum chamfer dimension
T_1	23,8 mm	Height of the housing washer
T_3	31 mm	Height of the shaft washer
T_5	42,5 mm	Distance shaft washer - cage
A	44,8 mm	Distance of the center point

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna