





3001-2RS

Angular contact ball bearing

Angular contact ball bearing 30...-B-2RS-TVH,
double row, seals, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	28 mm	Outside diameter
B	12 mm	Width
C _r	6.100 N	Basic dynamic load rating, radial
C _{0r}	3.700 N	Basic static load rating, radial
C _{ur}	193 N	Fatigue load limit, radial
n _G	15.800 1/min	Limiting speed
≈m	0,033 kg	Masa



Mounting dimensions

$d_{a\ min}$	14 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	26 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,3 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	0,3 mm	Minimum chamfer dimension
$D_{\ 1}$	22,5 mm	Shoulder diameter outer ring
$D_{\ 2}$	23,16 mm	Caliber diameter outer ring
$d_{\ 1}$	17,6 mm	Shoulder diameter inner ring
$d_{\ 2}$	16,4 mm	Caliber diamter inner ring
a	13,5 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

$T_{\ min}$	-20 °C	Operating temperature min.
$T_{\ max}$	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne