




FAG

32004-X-H

Tapered roller bearing

Tapered roller bearings 320, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	42 mm	Outside diameter
B	15 mm	Width, inner ring
C	12 mm	Width, outer ring
T	15 mm	Width, total
C _r	22.800 N	Basic dynamic load rating, radial
C _{0r}	28.500 N	Basic static load rating, radial
C _{ur}	3.100 N	Fatigue load limit, radial
n _G	14.480 1/min	Limiting speed
n _{gr}	10.800 1/min	Thermal speed rating
≈m	101 g	Masa



Mounting dimensions

d _a max	25 mm	Maximum diameter of shaft shoulder
d _b min	25 mm	Minimum diameter of shaft shoulder
D _a min	36 mm	Minimum diameter of housing shoulder
D _a max	37 mm	Maximum diameter of housing shoulder
D _b min	39 mm	Minimum diameter of housing shoulder
C _a min	3 mm	Minimum axial space
C _b min	3 mm	Minimum axial space
r _a max	0,6 mm	Maximum fillet radius of shaft
r _b max	0,6 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	0,6 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	0,6 mm	Minimum chamfer dimension of outer ring back face
a	10 mm	Distance between the apexes of the pressure cones
d ₁ max	33,8 mm	Maximum guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,37	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,6	Dynamic axial load factor
Y ₀	0,88	Static axial load factor

Additional information

T3CC020	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia