



FAG

32044-X-XL>A

Tapered roller bearing

Tapered roller bearings 320, main dimensions
acc. to DIN 720, separable

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	XL	X-life
Version code	>A	Not marked on bearing
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	340 mm	Outside diameter
B	76 mm	Width, inner ring
C	57 mm	Width, outer ring
T	76 mm	Width, total
C _r	1.060.000 N	Basic dynamic load rating, radial
C _{0r}	1.640.000 N	Basic static load rating, radial
C _{ur}	207.000 N	Fatigue load limit, radial
n _G	2.290 1/min	Limiting speed
n _{gr}	1.130 1/min	Thermal speed rating
m	24,2 kg	Masa



Mounting dimensions

d _a max	243 mm	Maximum diameter of shaft shoulder
d _b min	234 mm	Minimum diameter of shaft shoulder
D _a min	300 mm	Minimum diameter of housing shoulder
D _a max	326 mm	Maximum diameter of housing shoulder
D _b min	326 mm	Minimum diameter of housing shoulder
C _a min	12 mm	Minimum axial space
C _b min	19 mm	Minimum axial space
r _a max	4 mm	Maximum fillet radius of shaft
r _b max	3 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	4 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	3 mm	Minimum chamfer dimension of outer ring back face
a	73 mm	Distance between the apexes of the pressure cones
d ₁	278,5 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,43	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,39	Dynamic axial load factor
Y ₀	0,77	Static axial load factor

Additional information

T4FD220	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



łożysko gabarytowe