



FAG





X-life

3207-BD-XL-2Z-C3

Angular contact ball bearing

Angular contact ball bearing 32...BD-XL-2Z, double row, X-life, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Type of Seal	2Z	Non-contact shield on both sides
Cage	JH	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	72 mm	Outside diameter
B	27 mm	Width
C _r	41.000 N	Basic dynamic load rating, radial
C _{0r}	30.000 N	Basic static load rating, radial
C _{ur}	2.090 N	Fatigue load limit, radial
n _G	7.600 1/min	Limiting speed
n _{gr}	9.900 1/min	Reference speed
≈m	0,451 kg	Masa



Mounting dimensions

$d_{a\min}$	42 mm	Minimum diameter shaft shoulder
$D_{a\max}$	65 mm	Maximum diameter of housing shoulder
$r_{a\max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
D_1	62,4 mm	Shoulder diameter outer ring
D_2	65,39 mm	Caliber diameter outer ring
d_1	49,1 mm	Shoulder diameter inner ring
d_2	46,93 mm	Caliber diamter inner ring
a	42,5 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne