



FAG

32314-DY

Tapered roller bearing

Tapered roller bearings 323, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	150 mm	Outside diameter
B	51 mm	Width, inner ring
C	42 mm	Width, outer ring
T	54 mm	Width, total
C _r	290.000 N	Basic dynamic load rating, radial
C _{0r}	370.000 N	Basic static load rating, radial
C _{ur}	46.000 N	Fatigue load limit, radial
n _G	4.800 1/min	Limiting speed
n _{gr}	3.650 1/min	Thermal speed rating
≈m	4.230 g	Masa



Mounting dimensions

d a max	86 mm	Maximum diameter of shaft shoulder
d b min	82 mm	Minimum diameter of shaft shoulder
D a min	125 mm	Minimum diameter of housing shoulder
D a max	138 mm	Maximum diameter of housing shoulder
D b min	140 mm	Minimum diameter of housing shoulder
C a min	6 mm	Minimum axial space
C b min	12 mm	Minimum axial space
r a max	3 mm	Maximum fillet radius of shaft
r b max	2,5 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	3 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	2,5 mm	Minimum chamfer dimension of outer ring back face
a	37 mm	Distance between the apexes of the pressure cones
d 1	107,7 mm	Guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,74	Dynamic axial load factor
Y 0	0,96	Static axial load factor

Additional information

T2GD070	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia