



FAG

32907-H

Tapered roller bearing

Tapered roller bearings 329, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	55 mm	Outside diameter
B	14 mm	Width, inner ring
C	11,5 mm	Width, outer ring
T	14 mm	Width, total
C _r	26.100 N	Basic dynamic load rating, radial
C _{0r}	38.000 N	Basic static load rating, radial
C _{ur}	4.100 N	Fatigue load limit, radial
n _G	10.560 1/min	Limiting speed
n _{gr}	7.000 1/min	Thermal speed rating
≈m	127 g	Masa



Mounting dimensions

d a max	40 mm	Maximum diameter of shaft shoulder
d b min	40 mm	Minimum diameter of shaft shoulder
D a min	50 mm	Minimum diameter of housing shoulder
D a max	50 mm	Maximum diameter of housing shoulder
D b min	52 mm	Minimum diameter of housing shoulder
C a min	3 mm	Minimum axial space
C b min	3 mm	Minimum axial space
r a max	0,6 mm	Maximum fillet radius of shaft
r b max	0,6 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	0,6 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	0,6 mm	Minimum chamfer dimension of outer ring back face
a	11 mm	Distance between the apexes of the pressure cones
d 1 max	47,4 mm	Maximum guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,29	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	2,06	Dynamic axial load factor
Y 0	1,13	Static axial load factor

Additional information

T2BD035	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia