



FAG


33013-XL

Tapered roller bearing

Tapered roller bearings 330, main dimensions  
acc. to DIN 720, separable

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                 |          |                                              |
|-----------------|----------|----------------------------------------------|
| Tolerance class | P6X      | Class 6X (ISO 492:2023)                      |
| Heat treatment  | Standard |                                              |
| Cage            | Standard | Sheet steel cage, window cage, roller-guided |
| Internal design | Standard |                                              |
| Quality level   | XL       | X-life                                       |
| Number of rows  | 1        | Single-row design                            |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 65 mm       | Bore diameter                     |
| D               | 100 mm      | Outside diameter                  |
| B               | 27 mm       | Width, inner ring                 |
| C               | 21 mm       | Width, outer ring                 |
| T               | 27 mm       | Width, total                      |
| C <sub>r</sub>  | 124.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 161.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 27.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 8.300 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.300 1/min | Thermal speed rating              |
| m               | 0,76 kg     | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \max}$ | 72 mm  | Maximum diameter of shaft shoulder   |
| $d_{b \min}$ | 72 mm  | Minimum diameter of shaft shoulder   |
| $D_{a \min}$ | 89 mm  | Minimum diameter of housing shoulder |
| $D_{a \max}$ | 93 mm  | Maximum diameter of housing shoulder |
| $D_{b \min}$ | 96 mm  | Minimum diameter of housing shoulder |
| $C_{a \min}$ | 5 mm   | Minimum axial space                  |
| $C_{b \min}$ | 6 mm   | Minimum axial space                  |
| $r_{a \max}$ | 1,5 mm | Maximum fillet radius of shaft       |
| $r_{b \max}$ | 1,5 mm | Maximum fillet radius of housing     |

### Dimensions

|                 |         |                                                   |
|-----------------|---------|---------------------------------------------------|
| $r_{1, 2 \min}$ | 1,5 mm  | Minimum chamfer dimension of inner ring back face |
| $r_{3, 4 \min}$ | 1,5 mm  | Minimum chamfer dimension of outer ring back face |
| $a$             | 21 mm   | Distance between the apexes of the pressure cones |
| $d_1$           | 83,8 mm | Guidance rib diameter of inner ring               |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,35 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y$   | 1,72 | Dynamic axial load factor                                                            |
| $Y_0$ | 0,95 | Static axial load factor                                                             |

### Additional information

T2CE065

Comparative designation to ISO 10317 and ISO 355



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia