



FAG

33021

Tapered roller bearing

Tapered roller bearings 330, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	105 mm	Bore diameter
D	160 mm	Outside diameter
B	43 mm	Width, inner ring
C	34 mm	Width, outer ring
T	43 mm	Width, total
C _r	265.000 N	Basic dynamic load rating, radial
C _{0r}	450.000 N	Basic static load rating, radial
C _{ur}	55.000 N	Fatigue load limit, radial
n _G	4.150 1/min	Limiting speed
n _{gr}	2.850 1/min	Thermal speed rating
≈m	3,021 kg	Masa



Mounting dimensions

d _a max	116 mm	Maximum diameter of shaft shoulder
d _b min	115 mm	Minimum diameter of shaft shoulder
D _a min	145 mm	Minimum diameter of housing shoulder
D _a max	150 mm	Maximum diameter of housing shoulder
D _b min	153 mm	Minimum diameter of housing shoulder
C _a min	7 mm	Minimum axial space
C _b min	9 mm	Minimum axial space
r _a max	2,5 mm	Maximum fillet radius of shaft
r _b max	2 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	2,5 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	2 mm	Minimum chamfer dimension of outer ring back face
a	31 mm	Distance between the apexes of the pressure cones
d ₁	131,5 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,28	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	2,12	Dynamic axial load factor
Y ₀	1,17	Static axial load factor

Additional information

T2DE105	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia