



**3808-2RS**

Angular contact ball bearing

Angular contact ball bearing 38..-B-2RS-TVH,
double row, seals, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	52 mm	Outside diameter
B	10 mm	Width
C _r	6.900 N	Basic dynamic load rating, radial
C _{0r}	7.600 N	Basic static load rating, radial
C _{ur}	430 N	Fatigue load limit, radial
n _G	6.100 1/min	Limiting speed
n _{gr}	6.300 1/min	Reference speed
≈m	0,046 kg	Masa



Mounting dimensions

d _{a min}	42 mm	Minimum diameter shaft shoulder
D _{a max}	50 mm	Maximum diameter of housing shoulder
r _{a max}	0,3 mm	Maximum fillet radius

Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
D ₁	48,54 mm	Shoulder diameter outer ring
D ₂	49,6 mm	Caliber diameter outer ring
d ₁	44,6 mm	Shoulder diameter inner ring
d ₂	43,54 mm	Caliber diamter inner ring
a	25,2 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne