




FAG

51226

Axial deep groove ball bearing

Axial deep groove ball bearing 512, single direction, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |    |                                         |
|----------------------------------|----|-----------------------------------------|
| Cage                             | JP | Steel sheet metal                       |
| Tolerance class                  | PN | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |

Main Dimensions & Performance Data

|                 |             |                                  |
|-----------------|-------------|----------------------------------|
| d               | 130 mm      | Inner diameter shaft washer      |
| D               | 190 mm      | Outer diameter housing washer    |
| T               | 45 mm       | Height                           |
| C <sub>a</sub>  | 184.000 N   | Basic dynamic load rating, axial |
| C <sub>0a</sub> | 540.000 N   | Basic static load rating, axial  |
| C <sub>ua</sub> | 19.500 N    | Fatigue load limit, axial        |
| n <sub>G</sub>  | 2.210 1/min | Limiting speed                   |
| n <sub>gr</sub> | 2.850 1/min | Reference speed                  |
| m               | 3,946 kg    | Masa                             |

Mounting dimensions

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 166 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 154 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 1,5 mm | Maximum filled radius                |



Dimensions

|                  |        |                               |
|------------------|--------|-------------------------------|
| r <sub>min</sub> | 1,5 mm | Minimum chamfer dimension     |
| D <sub>1</sub>   | 133 mm | Inner diameter housing washer |
| d <sub>1</sub>   | 187 mm | Outer diameter shaft washer   |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Calculation factors

|   |     |                     |
|---|-----|---------------------|
| A | 1,7 | Minimum load factor |
|---|-----|---------------------|

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|   | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |