




FAG

51340-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 513...-MP,
single direction, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	200 mm	Inner diameter shaft washer
D	340 mm	Outer diameter housing washer
T	110 mm	Height
C _a	620.000 N	Basic dynamic load rating, axial
C _{0a}	2.380.000 N	Basic static load rating, axial
C _{ua}	67.000 N	Fatigue load limit, axial
n _G	980 1/min	Limiting speed
n _{gr}	1.740 1/min	Reference speed
m	43 kg	Masa

Mounting dimensions

d _{a min}	284 mm	Minimum diameter shaft shoulder
D _{a max}	256 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum filled radius



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	205 mm	Inner diameter housing washer
d ₁	335 mm	Outer diameter shaft washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

A	30	Minimum load factor
---	----	---------------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe