




FAG

53207

Axial deep groove ball bearing

Axial deep groove ball bearing 532, single direction, with spherical housing washer, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu


|                                  |    |                                         |
|----------------------------------|----|-----------------------------------------|
| Cage                             | JP | Steel sheet metal                       |
| Tolerance class                  | PN | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |

Main Dimensions & Performance Data

|                 |             |                                  |
|-----------------|-------------|----------------------------------|
| d               | 35 mm       | Inner diameter shaft washer      |
| D               | 62 mm       | Outer diameter housing washer    |
| T               | 19,9 mm     | Height                           |
| C <sub>a</sub>  | 35.500 N    | Basic dynamic load rating, axial |
| C <sub>0a</sub> | 67.000 N    | Basic static load rating, axial  |
| C <sub>ua</sub> | 3.100 N     | Fatigue load limit, axial        |
| n <sub>G</sub>  | 6.000 1/min | Limiting speed                   |
| n <sub>gr</sub> | 8.000 1/min | Reference speed                  |
| ≈m              | 0,221 kg    | Masa                             |

Mounting dimensions

|                    |       |                                      |
|--------------------|-------|--------------------------------------|
| d <sub>a min</sub> | 51 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 48 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 1 mm  | Maximum filled radius                |



Dimensions

|                  |       |                                 |
|------------------|-------|---------------------------------|
| r <sub>min</sub> | 1 mm  | Minimum chamfer dimension       |
| D <sub>1</sub>   | 37 mm | Inner diameter housing washer   |
| d <sub>1</sub>   | 62 mm | Outer diameter shaft washer     |
| R                | 50 mm | Radius spherical housing washer |
| A                | 24 mm | Distance of the center point    |
| T <sub>1</sub>   | 22 mm | Height with seat washer         |
| D <sub>2</sub>   | 48 mm | Bore diameter seat washer       |
| D <sub>3</sub>   | 65 mm | Outside diameter seat washer    |
| C                | 7 mm  | Height seat washer              |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Calculation factors

|   |       |                     |
|---|-------|---------------------|
| A | 0,028 | Minimum load factor |
|---|-------|---------------------|

Additional information

|      |             |
|------|-------------|
| U207 | Seat washer |
|------|-------------|

Właściwości

|  |                                   |
|--|-----------------------------------|
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Nieosiowość statyczna             |