




FAG

53234-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 532...-MP, single direction, with spherical housing washer, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu


Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	170 mm	Inner diameter shaft washer
D	240 mm	Outer diameter housing washer
T	58,7 mm	Height
C _a	285.000 N	Basic dynamic load rating, axial
C _{0a}	930.000 N	Basic static load rating, axial
C _{ua}	29.500 N	Fatigue load limit, axial
n _G	1.740 1/min	Limiting speed
n _{gr}	2.230 1/min	Reference speed
≈m	7,92 kg	Masa

Mounting dimensions

d _{a min}	212 mm	Minimum diameter shaft shoulder
D _{a max}	200 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum filled radius



Dimensions

r_{min}	1,5 mm	Minimum chamfer dimension
D_1	173 mm	Inner diameter housing washer
d_1	237 mm	Outer diameter shaft washer
R	180 mm	Radius spherical housing washer
A	91 mm	Distance of the center point
T_1	65 mm	Height with seat washer
D_2	200 mm	Bore diameter seat washer
D_3	250 mm	Outside diameter seat washer
C	21,5 mm	Height seat washer

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Calculation factors

A	4,5	Minimum load factor
-----	-----	---------------------

Additional information

U234	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna