




FAG

54220 

Axial deep groove ball bearing

Axial deep groove ball bearing 542, double direction, with spherical housing washer, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu


Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	85 mm	Inner diameter shaft washer
D	150 mm	Outer diameter housing washer
T ₂	72,8 mm	Height
C _a	119.000 N	Basic dynamic load rating, axial
C _{0a}	325.000 N	Basic static load rating, axial
C _{ua}	13.300 N	Fatigue load limit, axial
n _G	2.700 1/min	Limiting speed
n _{gr}	3.550 1/min	Reference speed
≈m	3,905 kg	Masa

Mounting dimensions

d _{a max}	100 mm	Maximum diameter shaft shoulder
D _{a max}	125 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum filled radius
r _{a1 max}	1 mm	Maximum filled radius



Dimensions

D 1	103 mm	Inner diameter housing washer
B	15 mm	Height shaft washer
r min	1,1 mm	Minimum chamfer dimension
r 1 min	1 mm	Minimum chamfer dimension
R	112 mm	Radius spherical housing washer
A	49 mm	Distance of the center point
T 3	81 mm	Height with seat washer
D 2	125 mm	Bore diameter seat washer
D 3	155 mm	Outside diameter seat washer
C	14 mm	Height seat washer

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Calculation factors

A	0,68	Minimum load factor
---	------	---------------------

Additional information

U220	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna