


FAG

60/560-M-C3

Deep groove ball bearing

Deep groove ball bearing 60.-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	560 mm	Bore diameter
D	820 mm	Outside diameter
B	115 mm	Width
C _r	760.000 N	Basic dynamic load rating, radial
C _{0r}	1.540.000 N	Basic static load rating, radial
C _{ur}	36.500 N	Fatigue load limit, radial
n _G	1.260 1/min	Limiting speed
n _{gr}	950 1/min	Reference speed
≈m	209 kg	Masa



Mounting dimensions

d _{a min}	583 mm	Minimum diameter shaft shoulder
D _{a max}	797 mm	Maximum diameter of housing shoulder
r _{a max}	5 mm	Maximum fillet radius

Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	742 mm	Shoulder diameter outer ring
d ₁	642 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

f ₀	16	Calculation factor
----------------	----	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe