


**FAG****6002-C-2BRS-TVH-L178-C3>V** [🔗](#)

Deep groove ball bearing

Deep groove ball bearing 60...-C-2BRS-TVH,
single row, Generation C, shields, plastic
cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	2BRS	Non-contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L178	Grease (L178/customer specific)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	32 mm	Outside diameter
B	9 mm	Width
C _r	6.300 N	Basic dynamic load rating, radial
C _{0r}	2.850 N	Basic static load rating, radial
C _{ur}	191 N	Fatigue load limit, radial
n _G	31.500 1/min	Limiting speed
n _{gr}	23.200 1/min	Reference speed
≈m	0,029 kg	Masa



Mounting dimensions

d a min	17 mm	Minimum diameter shaft shoulder
D a max	30 mm	Maximum diameter of housing shoulder
r a max	0,3 mm	Maximum fillet radius

Dimensions

r min	0,3 mm	Minimum chamfer dimension
D 1	26,84 mm	Shoulder diameter outer ring
D 2	28,75 mm	Caliber diameter outer ring
d 1	20,16 mm	Shoulder diameter inner ring
d 2	19,18 mm	Caliber diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Calculation factors

f 0	14	Calculation factor
-----	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne