




FAG

6002-C-HRS-C3>V

Deep groove ball bearing

Deep groove ball bearing 60...-C-HRS, single row, Generation C, seal, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	HRS	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	32 mm	Outside diameter
B	9 mm	Width
C _r	6.300 N	Basic dynamic load rating, radial
C _{0r}	2.850 N	Basic static load rating, radial
C _{ur}	191 N	Fatigue load limit, radial
n _G	20.300 1/min	Limiting speed
≈m	0,028 kg	Masa



Mounting dimensions

$d_{a\ min}$	17 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	30 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,3 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	0,3 mm	Minimum chamfer dimension
D_1	26,84 mm	Shoulder diameter outer ring
D_2	28,75 mm	Caliber diameter outer ring
d_1	20,16 mm	Shoulder diameter inner ring
d_2	19,18 mm	Caliber diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	100 °C	Operating temperature max.

Calculation factors

f_0	14	Calculation factor
-------	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Uszczelnienie jednostronne