



FAG

6003-2RSR-L038-C3

Deep groove ball bearing

Deep groove ball bearing 60...-2RSR, single row, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L038	Grease (L038/customer specific)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	35 mm	Outside diameter
B	10 mm	Width
C _r	6.400 N	Basic dynamic load rating, radial
C _{0r}	3.250 N	Basic static load rating, radial
C _{ur}	162 N	Fatigue load limit, radial
n _G	11.800 1/min	Limiting speed
m	39,1 g	Masa

Mounting dimensions

d _{a min}	19 mm	Minimum diameter shaft shoulder
D _{a max}	33 mm	Maximum diameter of housing shoulder
r _{a max}	0,3 mm	Maximum fillet radius



Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
D_1	29,51 mm	Shoulder diameter outer ring
D_2	30,81 mm	Caliber diameter outer ring
d_1	22,65 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

Calculation factors

f_0	14,3	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne