





FAG

605-2Z-CO7-C3

Deep groove ball bearing

Deep groove ball bearing 60...-2Z, single row, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Logistical code	CO7	-
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	5 mm	Bore diameter
D	14 mm	Outside diameter
B	5 mm	Width
C _r	1.390 N	Basic dynamic load rating, radial
C _{0r}	495 N	Basic static load rating, radial
C _{ur}	30,5 N	Fatigue load limit, radial
n _G	60.000 1/min	Limiting speed
n _{gr}	50.000 1/min	Reference speed
≈m	0,003 kg	Masa



Mounting dimensions

$d_{a \min}$	6,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	12,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,2 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,2 mm	Minimum chamfer dimension
$D_1 \approx$	10,8 mm	Shoulder diameter outer ring
$D_2 \approx$	11,2 mm	Caliber diameter outer ring
$d_1 \approx$	7,2 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	12,5	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne