





FAG

6218-RSR

Deep groove ball bearing

Deep groove ball bearing 62...-RSR, single row, seal, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	RSR	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	30 mm	Width
C _r	102.000 N	Basic dynamic load rating, radial
C _{0r}	74.000 N	Basic static load rating, radial
C _{ur}	4.500 N	Fatigue load limit, radial
n _G	2.380 1/min	Limiting speed
m	2,21 kg	Masa

Mounting dimensions

d _{a min}	101 mm	Minimum diameter shaft shoulder
D _{a max}	149 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum fillet radius



Dimensions

r _{min}	2 mm	Minimum chamfer dimension
D ₁	138,84 mm	Shoulder diameter outer ring
D ₂	143,42 mm	Caliber diameter outer ring
d ₁	112,25 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Calculation factors

f ₀	14,6	Calculation factor
----------------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Uszczelnienie jednostronne