



FAG

6224-2RSR-C3

Deep groove ball bearing

Deep groove ball bearing 62...-2RSR, single row, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	215 mm	Outside diameter
B	40 mm	Width
C _r	154.000 N	Basic dynamic load rating, radial
C _{0r}	123.000 N	Basic static load rating, radial
C _{ur}	6.400 N	Fatigue load limit, radial
n _G	1.770 1/min	Limiting speed
m	5,72 kg	Masa

Mounting dimensions

d _{a min}	132 mm	Minimum diameter shaft shoulder
D _{a max}	203 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum fillet radius



Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
D ₁	185,04 mm	Shoulder diameter outer ring
D ₂	190,5 mm	Caliber diameter outer ring
d ₁	151,05 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Calculation factors

f ₀	14,8	Calculation factor
----------------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne