



FAG



6307-C-NR>V

Deep groove ball bearing

Deep groove ball bearing 63.-C-NR, single row, Generation C, steel sheet metal cage, ring grove, snap ring



Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	Without	Not sealed
Design, bearing outer ring	NR	Ring groove for snap ring with snap ring
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical



Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	80 mm	Outside diameter
B	21 mm	Width
C _r	38.500 N	Basic dynamic load rating, radial
C _{0r}	19.100 N	Basic static load rating, radial
C _{ur}	1.320 N	Fatigue load limit, radial
n _G	13.600 1/min	Limiting speed
n _{gr}	10.900 1/min	Reference speed
m	0,424 kg	Masa

Mounting dimensions

d _{a min}	44 mm	Minimum diameter shaft shoulder
D _{a max}	71 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum fillet radius

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
D ₁	66,68 mm	Shoulder diameter outer ring
D ₂	69,68 mm	Caliber diameter outer ring
d ₁	48,86 mm	Shoulder diameter inner ring
d ₂	46,18 mm	Caliber diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	13,1	Calculation factor
----------------	------	--------------------



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia