

**FAG****6321-M-J20AB-C3** 

Deep groove ball bearing

Deep groove ball bearing 63...-M-J20AB,  
single row, solid brass cage, ceramic coated

## Informacje techniczne



## Twoja aktualna wersja produktu

|                                  |              |                                               |
|----------------------------------|--------------|-----------------------------------------------|
| Sealing                          | Without      | Not sealed                                    |
| Cage                             | M            | Solid brass cage, rolling element guided      |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                         |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150°       |
| Lubricant                        | Without      | Bearing not greased                           |
| Radial internal clearance        | C3 (Group 3) | Internal clearance larger than CN             |
| Bore type                        | Z            | Cylindrical                                   |
| Coating                          | J20AB        | Current insulation, outer ring ceramic coated |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 105 mm      | Bore diameter                     |
| D               | 225 mm      | Outside diameter                  |
| B               | 49 mm       | Width                             |
| C <sub>r</sub>  | 188.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 150.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 8.100 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5.300 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.450 1/min | Reference speed                   |
| ≈m              | 9,6 kg      | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a\ min}$ | 119 mm | Minimum diameter shaft shoulder      |
| $D_{a\ max}$ | 211 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 2,5 mm | Maximum fillet radius                |

### Dimensions

|             |          |                              |
|-------------|----------|------------------------------|
| $r_{\ min}$ | 3 mm     | Minimum chamfer dimension    |
| $D_1$       | 188,5 mm | Shoulder diameter outer ring |
| $d_1$       | 144,3 mm | Shoulder diameter inner ring |

### Temperature range

|             |        |                            |
|-------------|--------|----------------------------|
| $T_{\ min}$ | -30 °C | Operating temperature min. |
| $T_{\ max}$ | 150 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,7 | Calculation factor |
|-------|------|--------------------|

### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Izolowane