



FAG





X-life

7214-B-XL-MP

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-MP,  
single row, X-life, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |         |                                         |
|----------------------------------|---------|-----------------------------------------|
| Design variant                   | B       | B                                       |
| Sealing                          | Without | Not sealed                              |
| Cage                             | MP      | Solid brass cage, ball guided           |
| Tolerance class                  | PN      | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | S0      | Rings dimensional stabilized up to 150° |
| Lubricant                        | Without | Bearing not greased                     |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 70 mm       | Bore diameter                     |
| D               | 125 mm      | Outside diameter                  |
| B               | 24 mm       | Width                             |
| C <sub>r</sub>  | 71.000 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 58.000 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 4.050 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 9.400 1/min | Limiting speed                    |
| n <sub>gr</sub> | 5.500 1/min | Reference speed                   |
| ≈m              | 1,207 kg    | Masa                              |



Mounting dimensions

|               |          |                                      |
|---------------|----------|--------------------------------------|
| $d_{a\ min}$  | 79 mm    | Minimum diameter of shaft shoulder   |
| $D_{a\ max}$  | 116 mm   | Maximum diameter of housing shoulder |
| $D_{b\ max}$  | 119,4 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$  | 1,5 mm   | Maximum fillet radius of shaft       |
| $r_{a1\ max}$ | 1 mm     | Maximum fillet radius of housing     |

Dimensions

|              |           |                                                   |
|--------------|-----------|---------------------------------------------------|
| $r_{\min}$   | 1,5 mm    | Minimum chamfer dimension                         |
| $r_{1\ min}$ | 1 mm      | Minimum chamfer dimension                         |
| $D_1$        | 104,04 mm | Shoulder diameter on outer ring wide side face    |
| $d_1$        | 92,32 mm  | Shoulder diameter on inner ring wide side face    |
| $a$          | 52,9 mm   | Distance between the apexes of the pressure cones |
| $\alpha$     | 40 °      | Contact angle                                     |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |