



FAG



X-life

7326-B-XL-MP-UB

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-MP, single row, X-life, solid brass cage


Informacje techniczne

Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UB	Bearing set with smaller axial internal clearance than UA
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	58 mm	Width
C _r	305.000 N	Basic dynamic load rating, radial
C _{0r}	325.000 N	Basic static load rating, radial
C _{ur}	15.900 N	Fatigue load limit, radial
n _G	4.000 1/min	Limiting speed
n _{gr}	2.600 1/min	Reference speed
≈m	16,718 kg	Masa





Mounting dimensions

$d_{a\ min}$	147 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	263 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	271 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	1,5 mm	Maximum fillet radius of housing

Dimensions

$r_{\ min}$	4 mm	Minimum chamfer dimension
$r_{1\ min}$	1,5 mm	Minimum chamfer dimension
D_1	222,5 mm	Shoulder diameter on outer ring wide side face
d_1	188,5 mm	Shoulder diameter on inner ring wide side face
a	115 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Additional information

Tol (+)	12 µm	Tolerance for axial clearance or preload per set
$A_{\ min}$	34 mm	Axial clearance per set min.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia