




FAG

7602050-TVP

Axial angular contact ball bearing

Axial angular contact ball bearing 7602...-TVP, single direction, no screw mounting

Informacje techniczne



Twoja aktualna wersja produktu

|                         |          |                |
|-------------------------|----------|----------------|
| Cage                    | TVP      | Plastic cage   |
| Sealing                 | Without  |                |
| Arrangement bearing set | Standard | Single bearing |
| Lubricant               | Without  | Not greased    |

Main Dimensions & Performance Data

|                          |             |                                       |
|--------------------------|-------------|---------------------------------------|
| d                        | 50 mm       | Bore diameter                         |
|                          | 0 mm        | Bore diameter upper tolerance         |
|                          | -0,006 mm   | Bore diameter lower tolerance         |
| D                        | 90 mm       | Outside diameter                      |
|                          | 0 mm        | Outside diameter upper tolerance      |
|                          | -0,008 mm   | Outside diameter lower tolerance      |
| B                        | 20 mm       | Width                                 |
|                          | 0 mm        | Width upper tolerance                 |
|                          | -0,12 mm    | Width lower tolerance                 |
| C <sub>a</sub>           | 41.000 N    | Basic dynamic load rating, axial      |
| C <sub>0a</sub>          | 122.000 N   | Basic static load rating, axial       |
| C <sub>ua</sub>          | 5.600 N     | Fatigue load limit, axial             |
| n <sub>G</sub><br>Grease | 4.300 1/min | Limiting speed for grease lubrication |
| n <sub>g</sub>           | 2.400 1/min | Thermally safe operating speed        |
| ≈m                       | 0,575 kg    | Masa                                  |



Mounting dimensions

|                |       |                               |
|----------------|-------|-------------------------------|
| D <sub>a</sub> | 79 mm | Diameter of housing           |
| D <sub>a</sub> | H12   | Diameter of housing clearance |
| d <sub>a</sub> | 63 mm | Diameter shaft                |
| d <sub>a</sub> | h12   | Diameter shaft clearance      |

Dimensions

|                    |         |                                                   |
|--------------------|---------|---------------------------------------------------|
| r <sub>min</sub>   | 1,1 mm  | Minimum chamfer dimension                         |
| r <sub>1 min</sub> | 1,1 mm  | Minimum chamfer dimension                         |
| a                  | 71,5 mm | Distance between the apexes of the pressure cones |
| α                  | 60 °    | Contact angle                                     |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |

Additional information

|                 |            |                                                             |
|-----------------|------------|-------------------------------------------------------------|
| M <sub>R</sub>  | 0,23 Nm    | Bearing frictional torque                                   |
| c <sub>aL</sub> | 1.360 N/μm | Rigidity axial                                              |
|                 | 2 μm       | Axial runout                                                |
|                 | ZM50       | Recommended INA precision locknut for radial locking        |
|                 | AM50       | Recommended INA precision locknut for axial locking         |
| M <sub>A</sub>  | 85 Nm      | Tightening torque for the recommended INA precision locknut |
|                 | 16.810 N   | Required locknut force axial                                |



### Właściwości

---



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Bez uszczelnienia