



811/530-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 811...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	530 mm	Bore diameter
T	85 mm	Height
C _a	2.140.000 N	Basic dynamic load rating, axial
C _{0a}	10.500.000 N	Basic static load rating, axial
C _{ua}	790.000 N	Fatigue load limit, axial
n _G	485 1/min	Limiting speed
n _{gr}	120 1/min	Reference speed
D	640 mm	Outside diameter
m	64,44 kg	Masa

Mounting dimensions

r _{a max}	3 mm	Maximum recess radius
--------------------	------	-----------------------

Dimensions

D ₁	535 mm	Bore diameter housing washer
d ₁	635 mm	Rip diameter shaft washer
r _{min}	3 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K811/530-M	Axial roller and cage assembly
GS811/530	Housing Washer
WS811/530	Shaft washer

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia