





81176-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 811...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	380 mm	Bore diameter
T	65 mm	Height
C _a	1.170.000 N	Basic dynamic load rating, axial
C _{0a}	5.400.000 N	Basic static load rating, axial
C _{ua}	430.000 N	Fatigue load limit, axial
n _G	690 1/min	Limiting speed
n _{gr}	238 1/min	Reference speed
D	460 mm	Outside diameter
m	23,2 kg	Masa

Mounting dimensions

d _{a min}	454 mm	Minimum diameter shaft shoulder
D _{a max}	394 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius



Dimensions

D ₁	384 mm	Bore diameter housing washer
d ₁	456 mm	Rip diameter shaft washer
r _{min}	2 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81176-M	Axial roller and cage assembly
GS81176	Housing Washer
WS81176	Shaft washer

Właściwości

- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia