





81272-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	360 mm	Bore diameter
T	110 mm	Height
C _a	2.700.000 N	Basic dynamic load rating, axial
C _{0a}	10.700.000 N	Basic static load rating, axial
C _{ua}	850.000 N	Fatigue load limit, axial
n _G	650 1/min	Limiting speed
n _{gr}	197 1/min	Reference speed
D	500 mm	Outside diameter
m	71,13 kg	Masa

Mounting dimensions

d _{a min}	492 mm	Minimum diameter shaft shoulder
D _{a max}	393 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius



Dimensions

D ₁	365 mm	Bore diameter housing washer
d ₁	495 mm	Rip diameter shaft washer
r _{min}	4 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81272-M	Axial roller and cage assembly
GS81272	Housing Washer
WS81272	Shaft washer

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia