



89322-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 893..-M, two-row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	190 mm	Outside diameter
T	48 mm	Height
C _a	510.000 N	Basic dynamic load rating, axial
C _{0a}	1.870.000 N	Basic static load rating, axial
C _{ua}	181.000 N	Fatigue load limit, axial
n _G	1.920 1/min	Limiting speed
n _{gr}	790 1/min	Reference speed
m	6,305 kg	Masa

Mounting dimensions

d _a	186 mm	Minimum diameter shaft shoulder
D _a	120 mm	Maximum diameter of housing shoulder
r _a	2 mm	Recess radius



Dimensions

D ₁	113 mm	Bore diameter housing washer
d ₁	190 mm	Rip diameter shaft washer
B	48 mm	Width
r _{min}	2 mm	Minimum chamfer dimension
D _{c1}	110 mm	Cage bore diameter

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K89322-M	Axial roller and cage assembly
GS89322	Housing Washer
WS89322	Shaft washer

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia