


89330-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 893..-M, two-row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	250 mm	Outside diameter
T	60 mm	Height
C _a	840.000 N	Basic dynamic load rating, axial
C _{0a}	3.350.000 N	Basic static load rating, axial
C _{ua}	310.000 N	Fatigue load limit, axial
n _G	1.440 1/min	Limiting speed
n _{gr}	540 1/min	Reference speed
m	13,076 kg	Masa

Mounting dimensions

d _a	245 mm	Minimum diameter shaft shoulder
D _a	162 mm	Maximum diameter of housing shoulder
r _a	2,1 mm	Recess radius



Dimensions

D ₁	154 mm	Bore diameter housing washer
d ₁	250 mm	Rip diameter shaft washer
B	60 mm	Width
r _{min}	2,1 mm	Minimum chamfer dimension
D _{c1}	150 mm	Cage bore diameter

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K89330-M	Axial roller and cage assembly
GS89330	Housing Washer
WS89330	Shaft washer

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia