


89334-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 893..-M, two-row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	280 mm	Outside diameter
T	67 mm	Height
C _a	1.000.000 N	Basic dynamic load rating, axial
C _{0a}	4.050.000 N	Basic static load rating, axial
C _{ua}	365.000 N	Fatigue load limit, axial
n _G	1.280 1/min	Limiting speed
n _{gr}	475 1/min	Reference speed
m	18,373 kg	Masa

Dimensions

D ₁	174 mm	Bore diameter housing washer
d ₁	280 mm	Rip diameter shaft washer
r _{min}	3 mm	Minimum chamfer dimension
D _{c1}	280 mm	Cage bore diameter



Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K89334-M	Axial roller and cage assembly
GS89334	Housing Washer
WS89334	Shaft washer

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia