


89336-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 893..-M, two-row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	300 mm	Outside diameter
T	73 mm	Height
C _a	1.260.000 N	Basic dynamic load rating, axial
C _{0a}	5.100.000 N	Basic static load rating, axial
C _{ua}	465.000 N	Fatigue load limit, axial
n _G	1.200 1/min	Limiting speed
n _{gr}	405 1/min	Reference speed
m	23,52 kg	Masa

Dimensions

D ₁	184 mm	Bore diameter housing washer
d ₁	300 mm	Rip diameter shaft washer
B	73 mm	Width
r _{min}	3 mm	Minimum chamfer dimension
D _{c1}	180 mm	Cage bore diameter



Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K89336-M	Axial roller and cage assembly
GS89336	Housing Washer
WS89336	Shaft washer

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia