




ARCALUB-C2-2P-OIL-24VDC

Automatic lubricator CONCEPT

CONCEPT2, Multi-point lubricator

Informacje techniczne



Twoja aktualna wersja produktu

Drive System	PP	Piston pump
Lubricant volume	V250/300	250/300 cm³

Technical data

	Piston pump	Functional principle
V Lub	300 cm³	Lubricant volume
	0,15 cm³	Metering quantity (per outlet and stroke/impulse)
P op	50 bar	Operating pressure, max.
	Lubricating oil > 68 mm²/s	Lubricant
n pb	2	Number of pump bodies
n out	2	Number of outlets
	≤ 2	Number of lubrication points: direct
	≤ 4	Number of lubrication points: with splitters
	> 4	Number of lubrication points: with progressive distributors
	PA hose	Connection
U op	DC 24 V	Operating voltage
	M12 x 1, 4 pin	Connection plug for multi-function interface
I max	<= 250 mA	Current consumption (DC 24 V)
	microelectronic	Controller (integrated)
	PLC	Controller (extern)
	Integrated, electronic	Monitoring: pressure
	External (PLC)	Monitoring: fill level
	Empty level, back pressure, internal error (PLC)	Error message
	IP54	Protection class
	Polyamide	Housing material
t min	-20 °C	Operating temperature, min.
t max	70 °C	Operating temperature, max.
	vertical	Mounting position