


ARCALUB-X.CHAIN-PINION-12B2-Z8-G [🔗](#)

Chain lubrication pinion

Chain lubrication pinion duplex, Lubricant feed axial

Informacje techniczne



Twoja aktualna wersja produktu

|         |         |                                          |
|---------|---------|------------------------------------------|
| Version | AB-/B-2 | Chain lubrication pinions, duplex design |
|---------|---------|------------------------------------------|



Technical data

|                 |                                               |                                                            |
|-----------------|-----------------------------------------------|------------------------------------------------------------|
|                 | Lubrication of chains                         | Usage                                                      |
|                 | Duplex (double-row)                           | Design                                                     |
|                 | axial                                         | Lubricant feed                                             |
|                 | Pinion: plastic, roller:<br>open cell PU foam | Material                                                   |
| t <sub>op</sub> | 0 °C ... +60 °C                               | Operating temperature                                      |
|                 | 7 m/s                                         | Max. permissible circumferential speed at outside diameter |
|                 | Oil                                           | Lubricant                                                  |
|                 | 12 B-2                                        | Chain type according to ISO 606                            |
| z               | 8                                             | Teeth number                                               |
| d               | 49,78 mm                                      | Pitch circle diameter                                      |
| d <sub>a</sub>  | 55 mm                                         |                                                            |
| d <sub>b</sub>  | 36 mm                                         |                                                            |
| B <sub>1</sub>  | 29 mm                                         |                                                            |
| B <sub>2</sub>  | 5 mm                                          |                                                            |
| B <sub>3</sub>  | 15 mm                                         |                                                            |
| L <sub>1</sub>  | 30 mm                                         |                                                            |
| L <sub>2</sub>  | 41 mm                                         |                                                            |
| L <sub>3</sub>  | 55,5 mm                                       |                                                            |
| L <sub>4</sub>  | 71,2 mm                                       |                                                            |
| G <sub>1</sub>  | M10                                           | Thread                                                     |
| G <sub>2</sub>  | M6                                            | Thread                                                     |
| W               | 15 mm                                         | Width across flats                                         |
| ≈m              | 400 g                                         | Masa                                                       |