


**ARCALUB-X.PINION-MD6,0-Z17-B60-G-G**

Lubrication gear wheel

Lubrication gear straight teeth, lubricant feed  
axial

## Informacje techniczne



## Twoja aktualna wersja produktu

|         |   |                                   |
|---------|---|-----------------------------------|
| Version | G | Lubrication gears, straight teeth |
|---------|---|-----------------------------------|

## Technical data

|                 |                             |                                                            |
|-----------------|-----------------------------|------------------------------------------------------------|
|                 | Relubrication of tooth sets | Usage                                                      |
|                 | straight teeth              | Design                                                     |
|                 | axial                       | Lubricant feed                                             |
|                 | open cell PU foam           | Material                                                   |
| t <sub>op</sub> | -30 °C ... +140 °C          | Operating temperature                                      |
|                 | 5 m/s                       | Max. permissible circumferential speed at outside diameter |
|                 | Oil, greases up to NLGI 2   | Lubricant                                                  |
| m               | 6 mm                        | Modulus                                                    |
| z               | 17                          | Teeth number                                               |
| d               | 102 mm                      | Pitch circle diameter                                      |
| d <sub>a</sub>  | 114 mm                      |                                                            |
| B               | 60 mm                       |                                                            |
| L <sub>1</sub>  | 49 mm                       |                                                            |
| L <sub>2</sub>  | 75,7 mm                     |                                                            |
| L <sub>3</sub>  | 126,4 mm                    |                                                            |
| G <sub>1</sub>  | M16                         | Thread                                                     |
| G <sub>2</sub>  | M10x1                       | Thread                                                     |
| W               | 24 mm                       | Width across flats                                         |
| ≈m              | 0,7 kg                      | Masa                                                       |